

Wall pack lights or exterior building lights are terms that describe the outdoor lighting that is commonly mounted on the outside facing walls of buildings. This type of exterior lighting is generally used to provide illumination to ground areas frequented by vehicles and pedestrians, gardens, warehouses, public places, industrial areas, ...

WALL PACK LIGHTS

CATALOG 2022



WP211408



Mini Wall Pack
 Power Factor > 0.9
 Beam angle 120°
 CRI >80
 Photocell sensor optional
 Life time 50000 Hrs

100/277V AC 120/347V AC

Technical Data / Datos técnicos

Model	Rated Power	Chip	CCT	Efficiency	Input Voltage	Weight	Size(mm)
WP211408-15	15W	EPISTAR	2700-6500K	130lm/W	100-277V 120-347V 50-60Hz	1.1Kg	21.1*14.1*8.1cm
WP211408-20	20W	EPISTAR	2700-6500K	130lm/W	100-277V 120-347V 50-60Hz	1.1Kg	21.1*14.1*8.1cm
WP211408-25	25W	EPISTAR	2700-6500K	130lm/W	100-277V 120-347V 50-60Hz	1.1Kg	21.1*14.1*8.1cm

WP362319



Wall Pack
 Power Factor > 0.9
 Beam angle 120°
 CRI >80
 Photocell sensor optional
 Life time 50000 Hrs

100/277V AC 120/347V AC

Technical Data / Datos técnicos

Model	Rated Power	Chip	CCT	Efficiency	Input Voltage	Weight	Size(mm)
WP362319-30	30W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0Kg	360*230*195mm
WP362319-40	40W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0Kg	360*230*195mm
WP362319-60	60W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0Kg	360*230*195mm
WP362319-80	80W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0kg	360*230*195mm
WP362319-100	100W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	5.5Kg	360*230*195mm
WP362319-120	120W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	7Kg	360*230*195mm
WP452522-150	150W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	8kg	450*250*220mm

Application / Aplicaciones



nelux (HK) international,ltd

WP362319Q



Wall Pack
 Power Factor > 0.9
 Beam angle 120°
 CRI >80
 Photocell sensor optional
 Life time 50000 Hrs

100/277V AC 120/347V AC

Technical Data / Datos técnicos

Model	Rated Power	Chip	CCT	Efficiency	Input Voltage	Weight	Size(mm)
WP362319Q-30	30W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0Kg	360*230*195mm
WP362319Q-40	40W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0Kg	360*230*195mm
WP362319Q-60	60W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0Kg	360*230*195mm
WP362319Q-80	80W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	4.0kg	360*230*195mm
WP362319Q-100	100W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	5.5Kg	360*230*195mm
WP362319Q-120	120W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	7Kg	360*230*195mm
WP452522Q-150	150W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	8kg	450*250*220mm

WP201609



Adjustable Wall Pack
 Power Factor > 0.9
 Beam angle 120°
 CRI >80
 Photocell sensor optional
 Life time 50000 Hrs

100/277V AC 120/347V AC

Technical Data / Datos técnicos

Model	Rated Power	Chip	CCT	Efficiency	Input Voltage	Size(mm)
WP20169-30	30W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	205*165*98mm
WP20169-40	40W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	205*165*98mm
WP282111-60	60W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	280*216*110mm
WP362319Q-80	80W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	280*216*110mm
WP362319Q-100	100W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	330*267*124mm
WP362319Q-120	120W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	330*267*124mm

Application / Aplicaciones



nelux (HK) international,ltd

WP291317/WP332320



Full Cut off Wall Pack
 Power Factor > 0.9
 Beam angle 120°
 Photo cell sensor / 0-10V Dim optional
 347~480V/EM Back Up
 Life time 50000 Hrs

100/277V AC 120/347V AC

Technical Data / Datos técnicos

Model	Rated Power	Chip	CCT	Efficiency	Input Voltage	Size(mm)
WP291317-40	40W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	360*230*195mm
WP291317-60	60W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	360*230*195mm
WP332320-80	80W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	360*230*195mm
WP332320-100	100W	EPISTAR	2700-5700K	120lm/W	100-277V 120-347V 50-60Hz	360*230*195mm

Application / Aplicaciones



nelux (HK) international,ltd